



EWP-L SERIES SPECIFICATIONS


Engineered for both reliability and versatility, the **EWP-L** features external analog and simple digital pulse input control as well as manual control with an 1800:1 turndown ratio. Its high-speed 360 strokes-per-minute operation ensures consistent performance, while its robust priming capability and durable construction make it the optimal choice for any cost-effective, high-precision chemical injection applications.

Simple operation and adjustment with two control knobs, flowrates up to 6.7 GPH (25 l/h) and pressure capability to 175 psi (12 bar) enable the EWP-L to easily fit into most applications.

Flexible Installation

An optional quick-access mounting base* enables the EWP-L to be easily wall mounted or quickly removed from an installation without the need for tools.

*Mounting base (EP1015) sold separately




Rugged Housing

The EWP Series pumps are sealed and rated to an IP66 protection class (water and dust-proof) even without the chemical splash guard*.

*Splash guard cover (EP1014) sold separately



EWP MODEL IDENTIFICATION



PUMP SPECIFICATIONS

	Pump Capacity	Pump Head Code	Capacity mL/Min GPH		Pressure MPa PSI		Special Options	MAX SPM	Wet End
Standard Models	025	A	25	0.4	1.2	175	N	360	VC/VE/VF
	045	B	45	0.7	1.0	150	N/F	360	VC/VE/VF/PC/PA PE/FC/TA/TC/SH
	075	C	75	1.2	0.7	105	N/F	360	
	125	D	125	2.0	0.4	60	N/F	360	
	265	E	265	4.2	0.2	30	N	360	
	080	C	80	1.3	1.0	150	N/F	360	
	130	D	130	2.0	0.7	105	N/F	360	
	270	E	270	4.3	0.35	50	N	360	
	420	F	420	6.7	0.2	30	N	360	VC/VE/VF/PC/PA/PE
	420	F	410	6.5	0.2	30	N	360	TA/TC/FC/SH
Auto-Degassing Valve	035	B	35	0.6	1.0	150	A	360	VC/VE
	055	C	55	0.9	0.7	105	A	360	
	105	D	105	1.7	0.4	60	A	360	
	064	C	64	1.0	1.0	150	A	360	
	110	D	110	1.7	0.7	105	A	360	

WET END MATERIALS

Code	Pump Head	Valve Balls	Valve Seat	O-ring	Gasket	Diaphragm
VC	PVC	CE	FKM	FKM	PTFE	PCTFE (bonded to EPDM)
VE			EPDM	EPDM		
VF		PTFE				
PC	GFRPP	CE	FKM	FKM		
PE			EPDM	EPDM		
PA			PCTFE	AFLAS		
TC	PVDF		FKM	FKM		
TA			PCTFE	AFLAS		
FC						
SH	316SS	HC	316SS	—		

CE Alumina ceramic
FKM Fluoroelastomer
PTFE Polytetrafluoroethylene
PVDF Polyvinylidene Fluoride
EPDM Ethylene propylene diene monomer

GFRPP Glass Fiber Reinforced Polypropylene
PVC Polyvinylchloride (translucent)
HC Hastelloy C276
316SS Stainless Steel
AFLAS® Tetrafluoroethylene/propylene

All standard pumps include a manual air vent valve with the exception of FC liquid ends. All pumps include one foot valve, one injection valve, 20 feet of polyethylene tubing and one ceramic weight, with the exception of SH models.

ELECTRICAL SPECIFICATIONS

EWP-L

50/60 Hz, single phase
115 VAC $\pm 10\%$
230 VAC $\pm 10\%$

EWP-L (Capacity ends in 5)

13 Watt avg.
0.8 Amp max.
0.4 Amp max.

EWP-L (Other capacities)

23 Watt avg.
1.1 Amp max.
0.5 Amp max.

SHIPPING WEIGHT

Approx. 9 lbs. (4.1 kg)
(Plastic liquid ends)

Approx. 14 lbs. (6.4 kg)
(Stainless Steel liquid ends)

OPERATING CONDITIONS

Ambient Temperature: 32 to 122°F (0 to 50°C)

Liquid Temperature: PVC liquid ends: 32 to 104°F (0 to 40°C)
PP, PVDF, SS liquid ends: 32 to 140°F (0 to 60°C)
Below 32°F (0°C), pump is limited to 70% of maximum pressure.
Liquid cannot freeze.

Relative Humidity: 30% to 90% non-condensing

Pumps should always be shielded from direct exposure to the elements.

CONTROLLER SPECIFICATIONS

Controller Type		EWP-L
Operation Mode	MAN	0-100% stroke rate ^{Note1} (Max. 360 SPM)
	EXT	4-20 mA in proportion to 0-360 SPM
		0-6 Hz in synchronous with 0-360 SPM
Control Panel	Status LED	Red LED: Flashes when in EXT mode.
	LED	Green LED: Blinks synchronously with stroke when the pump is running.
		Red LED: Lights when a STOP signal is input.
	Speed/Control Dial	Speed/function dial (Stroke rate/PLS/ANA mode selector)
	Stroke Length Dial	Adjusts pump volume per stroke.
Control Functions	STOP	Stops pump with STOP input signal.
Input ^{Note4}	Pulse	Dry contact or open collector ^{Note2}
	Analogue	4-20 mADC (Input resistance 220 Ω)
	STOP	Dry contact or open collector ^{Note2}
Power Voltage		100 240 VAC 50/60 Hz ^{Note3}

Note 1: Use the stroke rate adjusting dial to change the operation functions. Dial scale is approximate for reference only.

Note 2: The maximum applied voltage to the contact is 5 VDC at 2.3 mA. The minimum application load of the relay or switch should be 1 mA or below.

Note 3: Observe the specified power voltage range or failure may result. The allowable power voltage range is 90–264 VAC.

Note 4: Input connectors sold separately. Use E90495 field-wired connector or IX0018 connector w/5m cable for ANA/DIG/STOP input.

Safety



Intertek

The EWP metering pumps are tested by Intertek to UL and CSA standards.



The EWP series metering pumps* are WQA tested and certified to NSF/ANSI/CAN Standard 61.


*See WWW.WQA.ORG for certified chemicals, parameters and MUL levels. NSF/ANSI/CAN 61 addresses health effects only. It does not address disinfection efficacy of the product.




EWP-L

Dimensions in mm


(VC/VS/VE/PC/PS/PE/TC)



(FC)



(SH)



(VC/VS/VE/PC/PS/PE/TC)

Model	(H)	(D)	(a)	(b)	(c)	(d)	(e)	(f)
EWP-038B								
EWP-080C	194	233		170	47	33	20	139
EWP-130D								
EWP-270E	207	235		172	47	35	4	168
EWP-420F	206			171			5	166

(FC)

Model	(H)	(D)	(a)	(b)	(c)	(d)	(e)	(f)
EWP-038B								
EWP-080C	162	199		170	13	33	35	121
EWP-130D								
EWP-270E				172				
EWP-410F	173	204		171	16	35	19	154

(SH)

Model	(H)	(D)	(a)	(b)	(c)	(d)	(e)	(f)
EWP-038B								
EWP-080C	197	204		170	15	32	40	111
EWP-130D								
EWP-270E	209	205					30	133
EWP-410F	211	207		170	15	34	27	138

Notes:

1. Illustrations shown represent B, C & D sizes.
2. The EWP-SH model liquid end is heavy. For additional support, a baseplate or base support rails are recommended.
3. The Multifunction valve increases the overall length (D) by 2.5mm, the discharge height (f) by 66.5mm, and the overall height (H) by 31.8mm.
2. The Auto-Degassing valve increases the overall height (H) and the discharge height (f) by 45.9mm



E90495



IX0018

E90495: DIN 5-Pin Field-wired Control Input Connector (ANA/DIG Inputs)

IX0018: DIN 5-PIN Control Input connector w/5m cable (ANA/DIG Inputs)